



GT06N

GPS Vehicle Crocker



Remote cut- off (petro I/power)

ComPeit the vehicle to stop by breaking off the fuel connection

Built - in 450mA h battery

High capacity Li-ion battery ensuring sufficient Dower supply



ATC detection for ignition status

Be aware of the ignition status whenever you need



SOS Emergency call

Thumb sized button allowing urgent call during an emergency case



Configurable tracking modes

Location uploaded following fixed distance, time interval. preset cornering



Multiple alarms

Instant alert for vibration, over speed, power off. Geo-fence



Voice monitor

Activate listen-in mode via text



Tracked by: SMS, APP, Web

Report location in real tame through Different interfaces

Application



GSM Specification

GSM frequency	850/ 900/1800 /1900 MHz
GPRS	class 12, TCP/ IP 32+32M b
Memory Phase error	RMSPE<5. PPE< 20
Max output	GSM850/GSM900: 33+3DBm GSM1800/GSM 900:30+36Bm
Max frequency error	+0 1pPm

GPS Specification

GPS chip	MTK high sensitivity chip,
Frequency GPS channel	L1, 1575. 42 MHz C/A code
Location accuracy tracking	66
sensitivity	<10 meters
Acquisition on sensitivity	-165dBm
TTF (open sky)	-148d 8dBm
	Avg. hot start 1sec Avg. cold start 32sec

Function & Package

Voice monitor range	<5meters
Battery	450mAh/ 3 7V Li-Polymer battery
Working voltage/current	9-36VDC/45mA (12VDC), 28mA (24VDC)
Standby time Working I me	60 hours
Operating temperature	4 hours
Device weight Device	-20 C 70 °C
dimension Box weight	96g
Box d mention	105 8(L)"54. 5(W)" 1d, 4(H) mm
	409g
	155(L)"95(W)"78(H) mm