



Product Description:

Specification

1. Small and light

Because of its small size and light weight, WeTrack 2 is easy to hide and install. This makes it so convenient for customers to use and carry.

2. Multifunctional

WeTrack 2's input voltage range is 9-90VDC, which makes it applicable for all vehicle types. It is multifunctional so that it can be put into use in electric cars, trucks etc.

3. Full-featured

WeTrack 2 is our brand-new product and it has all kinds of features in excellent quality at factory price. Therefore it can be used in many cases on different kinds of vehicles. Its cost-effectiveness makes it accessible to the majority of the target market.

Main Specifications:

GSM Band	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Antenna	Built-in GPS antenna, GSM quad-band antenna
LED Indicator	GSM-green, GPS-blue, Power-red
Battery	270mAh / 3.7V industrial grade lithium-polymer battery
Working voltage/current	9-90VDC/average 4.5mA(60VDC)
Standby time	50 hours
Size	78.0(L) x 41.0(W) x 13.0(H) mm
Weight	38g
Working Temperature	-20°C-70°C

GPS Specifications:

GPS chipset	MTK high sensitivity GPS chipset
Frequency	L1, 1575.42 MHz C/A code
Channels	66
Position accuracy	<10m
Track sensitivity	-165dBm
Capture sensitivity	-148dBm
Position time	Hot start : ≤ 2 sec(open sky); Cold start: ≤ 45 sec(open sky)